



Specification Sheet

7" Cased Hole Hydraulic System



The XpressDrill™ wellbore departure system provides a reliable sidetrack across a wide variety of wellbore conditions and applications. Solid anchoring into is achieved through the Extended Reach hydraulically set anchor. Bridge plugs, or other restrictions in the wellbore, are not required for successful operation. A 2.5-degree whipstock face ensures separation from the existing wellbore with minimal dogleg severity. The XpressMill™ milling assembly, dressed to full gauge with a combination of Premium PDC inserts and Tungsten Carbide, is designed to mill all casing grades and formations. Orientation can be achieved through MWD or Surface Read Gyro tools.

XpressDrill™ Whipstock Slide

Length	161.3"
Face Length	104.0"
OD	5.625"

Extended Reach Hydraulic Anchor

Max Tool OD, in (retracted)	5.625"
Max Tool OD, in (extended)	9.36"
Length	56.63"
Push capacity, lbs.	100,000
Maximum torque, ft.lbf	15,000

Running Tool


Length	70"
OD	4.75"
Connection up/down	3-1/2 API IF BOX

By-Pass Valve

Length	40.0"
OD	4.75"
Connection up/down	3-1/2 API IF BOX/ PIN

XpressMill™ Milling Assembly

Length	72"
Mill OD	6-1/8"
Fishing Neck OD	4.75"
Connection up	3-1/2 API IF PIN





Specification Sheet

7" Cased Hole Hydraulic System



The XpressDrill™ wellbore departure system provides a reliable sidetrack across a wide variety of wellbore conditions and applications. Solid anchoring into is achieved through the Extended Reach hydraulically set anchor. Bridge plugs, or other restrictions in the wellbore, are not required for successful operation. A 2.5-degree whipstock face ensures separation from the existing wellbore with minimal dogleg severity. The XpressMill™ milling assembly, dressed to full gauge with a combination of Premium PDC inserts and Tungsten Carbide, is designed to mill all casing grades and formations. Orientation can be achieved through MWD or Surface Read Gyro tools.

XpressDrill™ Whipstock Slide

Length	161.3"
Face Length	104.0"
OD	5.625"

Extended Reach Hydraulic Anchor

Max Tool OD, in (retracted)	5.625"
Max Tool OD, in (extended)	9.36"
Length	56.63"
Push capacity, lbs.	100,000
Maximum torque, ft.lbf	15,000

Running Tool

Length	70"
OD	4.75"
Connection up/down	3-1/2 API IF BOX

By-Pass Valve

Length	40.0"
OD	4.75"
Connection up/down	3-1/2 API IF BOX/ PIN

XpressMill™ Milling Assembly

Length	72"
Mill OD	6-1/8"
Fishing Neck OD	6-1/8"
Connection up	3-1/2 API IF PIN

